

MY	STYLE
----	-------

CONSTRUCTION	Brass Body (CuZn40Pb2), EN CW617N (Equivalent to BS CZ122); Zinc-Alloy Handles					
FINISHES	Chrome Plated to BS EN 248					
PRODUCT TYPE	Contemporary					
WATER PRESSURE	Min. 0.2 Max. 6.0 Bar					
PLUMBING SYSTEMS	Suitable for all Plumbing Systems, Hot and Cold Water Pressure Preferably Balanced; Max. Supply Pressure Differential Requirement No Greater than 5:1					
STANDARDS	Complies with BS5412, BS EN200					
CERTIFICATION	WRAS Approved and Certified					
CARTRIDGE	1/4 Turn 3/4" Ceramic Disc Valves					
NET WEIGHT (TAP ONLY)	1.85 Kg					
AERATOR	Spout Aerator					
FITTING	Brass G3/4" BSP Tails					
ADDITIONAL INFORMATION	Supplied with Chrome Stainless Steel, Double Interlock 1.5m Hose, Chrome Single Mode ABS Handset & Wall Mounted Holder					

Flow Rates (Litres per minute)

SYSTEM	0.1	0.2	0.3	0.5	1.0	1.5	2.0	3.0	4.0	5.0
PRESSURE	Bar	Bar	Bar	Bar	Bar	Bar	Bar	Bar	Bar	Bar
	7.3	7.6	-	9.0	11.3	13.2	14.9	18.7	-	







The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.